

Content Based Image Retrieval Techniques and Applications

Delia Smith^{#1}, Holly Willoughby^{#1}

^{#1}College of Engineering, Trivendrum, Kerala, Inida

¹deliasmith1994@gmail.com

²Hollyw1990@gmail.com

Abstract-In different PC vision applications broadly utilized is the procedure of recovering craved pictures from a substantial accumulation on the premise of elements that can be naturally extricated from the pictures themselves. These frameworks called CBIR (Content-Based Image Retrieval) have gotten escalated consideration in the writing of picture data recovery since this range was begun years prior, and thusly a wide scope of systems has been proposed.

Key Words: *Image Processing, Image Retrieval, Content based image search.*

I. INTRODUCTION:

A). *In CBIR (Content-Based Image Retrieval):* In CBIR visual elements, for example, shape, shading and composition are extricated to portray pictures. Each of the elements is spoken to utilizing one or more element descriptors. Amid the recovery, components and descriptors of the question are contrasted with those of the pictures in the database so as to rank each listed picture as per its separation to the inquiry. In biometrics frameworks pictures utilized as examples (e.g. unique mark, iris, hand and so forth.) are likewise represented by highlight vectors. The competitors examples are then recovered from database by contrasting the separation of their element vectors. The component extraction techniques for this application are examined.

In different PC vision applications broadly utilized is the procedure of recovering craved pictures from a substantial accumulation on the premise of elements that can be naturally extricated from the pictures themselves. These frameworks called CBIR (Content-Based Image Retrieval) have gotten escalated consideration in the writing of picture data recovery since this range was begun years prior, and thusly a wide scope of systems has been proposed.

There is need to locate a sought picture from an accumulation is shared by numerous expert gatherings, including writers, outline specialists and craftsmanship students of history. Amid the necessities of picture clients can change significantly, it can be valuable to represent picture questions into three levels of deliberation first is primitive elements, for example, shading or shape, second is consistent components, for example, the character of articles demonstrated and last is conceptual characteristics, for example, the hugeness of the scenes portrayed. While CBIR frameworks as of now work well just at the most minimal of these levels, most clients interest more elevated amounts of recovery.

An average CBIR framework consequently remove visual qualities like shading, shape, composition and spatial data of every picture in the database taking into account its pixel values and stores them into a different database inside of the framework called component database [1-5]. The element information for each of the visual traits of every picture is all that much littler in size contrasted with the picture information. The component database contains a reflection of the pictures in the picture database; every picture is spoken to by smaller representation of its substance like shading, composition, shape and spatial data as an altered length genuine esteemed multi-part highlight vectors or mark. The clients for the most part get ready inquiry picture and present to the framework. The framework consequently separate the visual properties of the question picture in the same mode as it accomplishes for every database picture and afterward distinguishes pictures in the database whose element vectors coordinate those of the inquiry picture, and sorts the best comparable articles as indicated by their closeness esteem. Amid operation the framework forms less reduced element vectors instead of extensive size picture information consequently giving CBIR its modest, quick and productive favourable position over content based recovery. CBIR framework can be utilized as a part of one of two ways. In the first place, precise picture

coordinating, that is coordinating two pictures, one a case picture and the other, picture in picture database. Besides is inexact picture coordinating, which is discovering most nearly match pictures to an inquiry picture [5-10].

CBIR includes the consequent four sections in framework acknowledgment, information accumulation, develop highlight database, look in the database, mastermind the request and manage the consequences of the recovery.

- Data get-together:-By utilizing Internet bug program that can gather networks naturally to meeting Internet and do the social event of the pictures on the site, then it will go over the various networks through the URL, rehashing this procedure and gathering all the pictures it has surveyed into the server.
- Extract component database:-Using file framework system do examination for the gathered pictures and concentrate the element data. As of now, the components that utilization generally include low-level elements, for example, shading, surface etc, the center level elements, for example, shape.
- Searching in the Database:-System remove the element of picture that sits tight for hunt when client include the picture test that need inquiry, then the internet searcher will look the suitable component from the database and figure the comparable separation, then locate some related networks and pictures with the least comparative separation.
- Process and record the outcomes:-Index the picture acquired from looking because of the comparability of elements, and after that profits the recovery pictures to the client and permit the client select. On the off chance that the client is not satisfied with the looking result, he can re-recovery the picture once more, and inquiries database once more.

The calculations utilized as a part of these frameworks are ordinarily partitioned into three errands:

- extraction,
- selection and
- classification

The extraction assignment changes rich substance of pictures into different substance highlights. Highlight extraction is the procedure of creating components to be utilized as a part of the determination and classification assignments. Highlight choice decreases the quantity of components gave to the characterization undertaking. Those components which are prone to help with segregation are chosen and utilized as a part of the order errand. Highlights which are not chose are tossed [10].

Among these three exercises, highlight extraction is most discriminating on the grounds that the specific elements made accessible for discrimination straightforwardly impact the viability of the arrangement task. The deciding consequence of the extraction undertaking is a situated of components, ordinarily called an element vector, which constitutes a representation of the picture.

In the most recent couple of years, various aforementioned frameworks utilizing picture substance highlight extraction advances demonstrated sufficiently dependable for expert applications in modern automation, biomedicine, social security, biometric authentication and crime prevention [10-12].

For every picture in the picture database, its elements are extricated and the got highlight space (or vector) is put away in the element database. At the point when an inquiry picture comes in, its element space will be contrasted and those in the component database one by one and the comparative pictures with the littlest element separation will be recovered.

CBIR can be separated in the accompanying stages:

- Pre-processing: The picture is initially handled to concentrate the elements, which depict its substance. The master censing includes separating, standardization, division, and item recognizable proof. The yield of this stage is a situated of noteworthy locales and items.
- Feature extraction: Features, for example, shape, composition, shading, and so forth are utilized to depict the substance of the picture. Picture elements can be arranged into primitives.

CBIR consolidates innovative components, for example,

- multimedia, flag and picture handling,
- pattern acknowledgment,
- human-PC collaboration,
- human recognition data sciences.

In Pattern Recognition we separate "important" data around an item through trials and utilize these estimations (= elements) to arrange an article. CBIR and direct protest acknowledgment, albeit comparable on a fundamental level, utilizing a large portion of the same picture examination/factual instruments, are altogether different operations. Object acknowledgment meets expectations with a current database of items and is principally a factual coordinating issue. One can contend that protest acknowledgment is an especially pleasantly characterized sub-set of CBIR

In CBIR, human components assume the crucial part. Another qualification in the middle of acknowledgment and recovery is obvious in less specific spaces - these applications are innately concerned with positioning (i.e., re-requesting database pictures as per their deliberate closeness to a question sample) instead of characterization (i.e., choosing procedure regardless

of whether a watched article coordinates a model), as the after effect of comparability based recovery.

Original CBIR frameworks were in view of manual text based annotation to speak to picture content. This system must be connected to little information volumes and, to be genuinely compelling, annotation must be restricted to extremely limit visual spaces.

In substance based picture recovery, pictures are naturally listed by producing a component vector (put away as a list in highlight databases) portraying the substance of the picture. The similitude of the component vectors of the question and database pictures is measured to recover the picture.

B). The Recovery Based On Clustering Techniques

Clustering procedures can be characterized into managed (counting semi-directed) and unsupervised plans. The previous comprises of progressive methodologies that request human connection to create part criteria for grouping. In unsupervised arrangement, called grouping or exploratory information examination, no named information are accessible [12-15]. The objective of Clustering procedures can be characterized into managed (counting semi-directed) and unsupervised plans. The previous comprises of progressive methodologies that request human connection to create part criteria for grouping. In unsupervised arrangement, called grouping or exploratory information examination, no named information are accessible [15-18]. The objective of clustering is to particular a limited unlabeled information set into a limited and discrete arrangement of "normal," concealed information structures, as opposed to give a precise portrayal of imperceptibly tests created from the same likelihood circulation [19]. It discriminately audits and condenses distinctive clustering methods. is to particular a limited unlabeled information set into a limited and discrete arrangement of "normal," concealed information structures, as opposed to give a precise portrayal of imperceptibly tests created from the same likelihood circulation. It discriminately audits and condenses distinctive clustering methods.

B.1) Relevance feedback:

An importance criticism methodology permits a client to communicate with the recovery calculation by giving the data of which pictures client believes are applicable to the inquiry. Keyword based picture recovery is performed by coordinating watchword as per client information and the pictures in the database. A few pictures might not have suitable essential words to depict them and hence the picture hunt will get to be complex. One of the arrangement keeping in mind the end goal to defeat this issue is "importance input" system that use client criticism and consequently lessens conceivable blunders and excess. This procedure utilizes a Bayesian classifier which manages positive and negative input.

Substance based bunching routines can't embrace to client changes, expansion of new points because of its static nature. To enhance the execution of data recovery log-based bunching methodologies are brought into the application.

B.2) Log –Based Clustering:

Pictures can be bunched in light of the recovery framework logs kept up by a data recovery process . The session keys are made and got to for recovery. Through this the session groups are made. Every session group produces log –based archive and similitude of picture couple is recovered. Log –based vector is made for every session vector taking into account the log-based documents. Presently, the session bunch is supplanted with this vector. The unaccessed archives makes its own vector. A mixture lattice is produced with no less than one individual report vector and one log-based bunched vector. Finally the mixture framework is bunched. This strategy is hard to perform on account of multidimensional pictures. To conquer this various leveled grouping is received.

B.3) Hierarchical Clustering

Distinctive levels Ref. This representation gives extremely educational depictions and perception for the potential information bunching structures, particularly when genuine progressive relations exist in the information, similar to the information from transformative research on distinctive types of organisms. HC calculations are primarily named agglomerative systems and divisive routines. Agglomerative grouping begins with groups and each of them incorporates precisely one article. A progression of consolidation operations are then taken after out that at long last lead all items to the same gathering. Divisive grouping continues in an inverse way. To start with, the whole information set fits in with a group and a method progressively partitions it until all groups are singleton bunches. For a bunch with articles, there are $2N-1-1$ conceivable two-subset divisions, which is extremely lavish in calculation. Along these lines, divisive bunching is not generally utilized as a part of practice. As of late, with the necessity for taking care of expansive scale information sets in information mining and different fields, numerous new HC methods have seemed and extraordinarily enhanced the grouping execution. Run of the mill illustrations incorporate CURE, ROCK ,Chameleon , and BIRCH .

Various leveled bunching (HC) calculations sort out information into a progressive structure as per the closeness network. The aftereffects of HC are typically portrayed by a twofold tree or dendrogram as demonstrated in Fig 1 where A, B, C, D, E, F, G are protests or bunches. It speaks to the settled gathering of examples and similitude levels at which groupings change. The root hub of the dendrogram speaks to the entire information set and every leaf hub is viewed as an information object. The transitional hubs, along these lines, portray the degree that the items are proximal to one another;

and the tallness of the dendrogram typically communicates the separation between every pair of articles or bunches, or an item and a group [19].

B.4) Retrieval Dictionary Based Clustering

An unpleasant characterization recovery framework is shaped. This is shaped by figuring the separation between two scholarly examples and these educated examples are ordered into distinctive bunches took after by a recovery stage. The principle downside tended to in this framework is the determination of the separation. To conquer this issue a recovery framework is created by recovery lexicon based grouping . This strategy has a recovery word reference era unit that arranges scholarly examples into plural bunches and makes a recovery lexicon utilizing the groups. Here, the picture is recovered in view of the separation between two circles with distinctive radii. Every range is a closeness measure between focal group and an information picture. A picture which is like the inquiry picture will be recovered utilizing recovery lexicon.

B.5) Ncut Algorithm

Ncut technique endeavors to arrange hubs into gatherings so that the inside of the gathering likeness is high, and/or between the gatherings comparability is low. This system is experimentally indicated to be moderately hearty in picture division . This system can be recursively connected to get more than two groups. In this system every time the subgraph with greatest number of hubs is apportioned (arbitrary choice for tie breaking). The procedure ends when the bound on the quantity of bunches is come to or the Ncut quality surpasses some edge T. The recursive Ncut allotment is basically a various leveled divisive bunching process that creates a tree. Regardless, the tree association here may deceiving a client in light of the fact that there is no assurance of any correspondence between the tree and the semantic structure of pictures. Moreover, sorting out picture groups into a tree structure will essentially confound the client interface.

B.6). K Means clustering

This nonhierairchal technique at first takes the quantity of parts of the populace equivalent to the last obliged number of bunches. In this stride itself the last obliged number of groups is picked such that the focuses are commonly most distant separated. Next, it analyzes every part in the populace and doles out it to one of the bunches relying upon the base separation. The centroid's position is recalculated everytime a part is added to the bunch and this proceeds until all the segments are assembled into the last obliged number of clusters. The K-implies calculation is exceptionally straightforward and can be effectively executed in tackling numerous useful issues. It can work extremely well for conservative and hyperspherical groups. The time

multifaceted nature of K-means is $O(NKd)$. Since K and d are generally considerably less than N, K-means can be utilized to bunch huge information sets. Parallel procedures for K-means are created that can to a great extent quicken the calculation. Incremental bunching procedures for instance (Bradley et al., 1998) don't require the capacity of the whole information set, and can deal with it in an one-example at once way. In the event that the example shows enough closeness to a group as per some predefined criteria, it is relegated to the bunch. Something else, another bunch is made to speak to the item.

B.7). Graph theory based clustering

The ideas and properties of diagram hypothesis make it exceptionally helpful to depict grouping issues by method for diagrams. Hubs of a weighted chart relate to information focuses in the example space and edges mirror the vicinities between every pair of information focuses. A diagram based grouping strategy is especially appropriate for managing information that is utilized as a part of the development of least spreading over tree MST. It can be utilized for recognizing bunches of any size and shape without indicating the genuine number of groups. No doubt understood calculations in bunching are Zhan's Minimum Spanning Tree based grouping, and grouping altering system , HCS calculation, and so forth. Flow exploration is centered around grouping utilizing partition and overcomes approach. Normally this grouping technique is utilized to identify unpredictable bunching limits in bunching results. Zhan proposes to build a MST and erase the conflicting edges, i.e. the edges weight qualities are essentially bigger than normal weight of the close-by edges in the tree. The irregularity measure is connected to every edge to distinguish and uproot the inconsistency edges, which comes about as an arrangement of disjoint subtrees, each subtree will speak to a different bunch

B.7) Divide and Conquer K-Means

At the point when the span of an information set is too huge, it is conceivable to separation the information into distinctive subsets and to utilize the chose group calculation independently to these subsets. This methodology is known as separation and vanquish . The separation and vanquish calculation first partitions the whole information set into a subset in view of some criteria. The chose subset is again bunched with a grouping calculation K-Means. The point of interest is to quicken seek and to diminish many-sided quality which relies on upon number of tests. Routines taking into account subspace grouping may help to facilitate the issue of bunching high-dimensional information, yet they are not adjusted at acquiring countless .A conceivable answer for this issue, is to bunch progressively (get a little number of groups and after that group again each of the bunches acquired). The proposed upgraded grouping system HDK which utilizes the blend of unsupervised bunching techniques is one of the

strategy that can generally quicken the CBIR framework. In next segment issue definition and structure depicts. In segments 3,4,5 and 6 development , late work ,open territories and after that conclusion are given individually.

B.8). Features Extraction

The component is characterized as an element of one or more measurements, each of which determines some quantifiable property of an item, and is registered such that it measures some noteworthy qualities of the article.

Highlight extraction is the heart of the substance based picture recovery. As we realize that crude picture information that cannot be utilized straightly as a part of most PC vision undertakings. Essentially two purpose for this most importantly, the high dimensionality of the picture makes it difficult to utilize the entire picture. Further reason is a considerable measure of the data implanted in the picture is excess. Thusly as opposed to utilizing the entire picture, just an expressive representation of the most critical data ought to concentrate. The procedure of discovering the expressive representation is known as highlight extraction and the subsequent representation is known as the element vector. Highlight extraction can be characterized as the demonstration of mapping the picture from picture space to the component space. Presently days, discovering great elements that well speak to a picture is still a troublesome undertaking. In this paper, a wide mixture of components are utilized for picture recovery from the database. Picture content can recognize visual and semantic substance. Components ordinarily speak to the visual substance. Visual substance can be further separated into general or area particular. For instance the elements that can use for looking would be speaking to the general visual substance like shading, composition, and shape. Another side, the components that are utilized for looking human countenances are space particular and may incorporate area learning. In the event that we discuss the semantic substance of a picture is not easy to concentrate. Annotation and/or particular deduction techniques in view of the visual substance additionally help to some degree in acquiring the semantic substance [2].

The primary point for picking the components to be extricated ought to be guided by the accompanying concerns: The elements ought to convey adequate data about the picture and ought not require any area particular learning and it ought to be anything but difficult to register all together for the way to deal with be doable for an expansive picture accumulation and quick recovery.

Something else is that it ought to relate well with the human perceptual attributes since clients will at long last focus the suitability of the recovered pictures

We arrange the different components presently utilized as takes after:

- General elements: Application autonomous components, for example, shading, composition, and shape. As indicated by the deliberation level, they can be further separated into:
 - Pixel-level elements: Features computed at every pixel, e.g. shading, area.
 - Local elements: Features computed over the re-sults of subdivision of the picture band on picture division or edge discovery.
 - Global elements: Features computed over the whole picture or simply consistent sub-region of a picture.
- Domain-particular elements: Application ward components, for example, human confronts, fingerprints, and applied features. These components are regularly a combination of low-level elements for a particular area.

Then again, all components can be coarsely ordered into low-level elements and abnormal state highlights. Low-level components can be extricated coordinated from the first pictures, though abnormal state highlight extraction must be taking into account low-level elements.

C.1) Colour

A standout amongst the most critical components of picture that make conceivable the acknowledgment of pictures by people is color[9]. Shading is a property that relies on upon the impression of light to the eye and the preparing of that data in the mind. We utilize shading ordinary to tell the refinement between items, spots, and the season of day .Images described by shading elements have numerous points of interest:

Productivity:-There is high rate of importance between the question picture and extricated coordinating pictures.

Quality:-The shading histogram is invariant to turn of the picture on the perspective hub and changes in little steps when turned generally or scaled.It is additionally not touchy to changes in picture and histogram determination and impediment.

Straightforwardness:-The development of the shading histogram is a straightforward procedure, including examining the picture, the determination of the histogram, relegating shading qualities to, and building the histogram utilizing shading segments as files.

Low Storage Requirements: - The shading histogram size is essentially littler than the picture itself, in view of shading quantization.

The shading component is a standout amongst the most generally utilized visual elements as a part of picture recovery. Pictures described by shading elements have numerous focal points:

- **Robustness.** The shading histogram is invariant to pivot of the picture on the perspective hub, and changes in little steps when pivoted generally or scaled [12,20]. It is likewise inhumane to changes in picture and histogram determination and impediment.
- **Effectiveness.** There is high rate of significance between the inquiry picture and the separated coordinating pictures.
- **Implementation effortlessness.** The development of the shading histogram is a direct process, including sweeping the picture, allocating shading qualities to the determination of the histogram, and building the histogram utilizing shading segments as lists.
- **Computational effortlessness.** The histogram reckoning has $O(X, Y)$ unpredictability for pictures of size $X \times Y$. The intricacy for a solitary picture match is direct, $O(n)$, where n speaks to the quantity of distinctive hues, or determination of the histogram.
- **Low capacity necessities.** The shading histogram size is essentially littler than the picture itself, accepting shading quantisation.




Fig. 0.1: The RGB colour space and the HSV and RGB colour space

Normally, the shading of a picture is spoken to through some shading model. There exist different shading model to portray shading data. A shading model is determined regarding 3-D coordinate framework and a subspace inside of that framework where every shading is spoken to by a solitary point. The all the more normally utilized shading models are RGB (red, green, blue), HSV (shade, immersion, worth) and Y, Cb, Cr (luminance and chrominance). Hence the shading substance is described by 3-channels from some shading model. One representation of shading substance of the picture is by utilizing shading histogram. Factually, it means the joint likelihood of the intensities of the three shading channels.

Shading is seen by people as a blend of three shading boosts: Red, Green, Blue, which frames a shading space (Fig. 1.1). This model has both a physiological establishment and an equipment related one. RGB hues are called essential hues and

are added substance. By changing their blends, different hues can be gotten. The representation of the HSV space (Fig. 1.1) is gotten from the RGB space 3D square, with the primary corner to corner of the RGB model, as the vertical hub in HSV. As immersion changes shape 0.0 to 1.0, the hues fluctuate from unsaturated (dim) to immersed (no white segment). Tone ranges from 0 to 360 degrees, with variety starting with red, experiencing yellow, green, cyan, blue and fuchsia and back to red. These shading spaces are instinctively comparing to the RGB model from which they can be determined through direct or non-linear transformations [19].

II. CONCLUSION:

In CBIR (Content-Based Image Retrieval), visual elements, for example, shape, shading and composition are extricated to portray pictures. Each of the elements is spoken to utilizing one or more element descriptors. Amid the recovery, components and descriptors of the question are contrasted with those of the pictures in the database so as to rank each listed picture as per its separation to the inquiry. In biometrics frameworks pictures utilized as examples (e.g. unique mark, iris, hand and so forth.) are likewise represented by highlight vectors. This paper has presented various parameters which impact content based retrieval techniques.

REFERENCES:

- [1] Naoto Miura, Akio Nagasaka, Takafumi Miyatake, "Feature extraction of finger vein patterns based on repeated line tracking and its application to personal identification", Springer-Verlag, 2004.
- [2] Naoto Miura, Akio Nagasaka, Takafumi Miyatake, "Extraction of Finger-Vein Patterns Using Maximum Curvature Points in Image Profiles", Conference on Machine Vision Applications, May 2005.
- [3] David Mulyono, Horng Shi Jinn, "A Study of Finger Vein Biometric for Personal Identification", IEEE, 2008.
- [4] Behnaz Saropourian, "A New Approach of Finger-Print Recognition based on Neural Network", IEEE, 2009.
- [5] Jinfeng Yang, Jinli Yang, Yihua Shi, "Finger-Vein Segmentation Based on Multi-channel Even-Symmetric Gabor Filters", IEEE, 2009.
- [6] Qin Bin Pan Jian-fei Cao Guag-zhong, Du Ge-guo, "The Anti-spoofing Study of Vein Identification System", IEEE, 2009.
- [7] Azadeh Noori Hoshyar, Riza Sulaiman, "Review on Finger Vein Authentication System by Applying Neural Network", IEEE, 2010.
- [8] Fengchun Zhang, Shuxu Guo, Xiaohua Qian, "Segmentation For Finger Vein Image Based On PDEs Denoising", International Conference on Biomedical Engineering and Informatics (BMEI), 2010.
- [9] Bhullar, Rohit K., et al. "Intelligent stress calculation and scheduling in segmented processor systems using buddy approach." Journal of Intelligent & Fuzzy Systems 32.4 (2017): 3129-3142.
- [10] Arora, Swinky, et al. "Novel stress calculation in parallel processor systems using buddy approach with enhanced short term CPU scheduling." Communication and Computing Systems. CRC Press, 2016. 663-672.
- [11] Bhullar, Rohit K., Lokesh Pawar, and Vijay Kumar. "A novel prime numbers based hashing technique for minimizing collisions." Next Generation Computing Technologies (NGCT), 2016 2nd International Conference on. IEEE, 2016.

- [12] Verma, Shiv Kumar, Manpreet Kaur, and Rohit Kumar. "Hybrid Image Fusion Algorithm Using Laplacian Pyramid and PCA Method." Proceedings of the Second International Conference on Information and Communication Technology for Competitive Strategies. ACM, 2016.
- [13] L. Pawar, R. Kumar, S. Arora, A. K. Manocha, "Optimized Route Selection On The Basis Of Discontinuity And Energy Consumption In Delay Tolerant Networks", Springer: Advances in Intelligent Systems and Computing, ISBN: 978-981-10-3769-6, 2016.
- [14] Kumar, Rohit et al." Advanced Replicated Hardware Architecture for Smartphones and Smart Devices" International Journal of Computational Intelligence Research,13.5 (2017) :805-813.
- [15] Kumar, Rohit, et al." Advanced Specialized Processor Architecture for Samrtphones" International Journal of Computational Intelligence Research, 13.5 (2017): 815-823.
- [16] Rohit Kumar "Pragmatic Implementation of Power Optimization in Wireless Sensor Networks " MATRIX Academic International Online Journal of Engineering and Technology 1.2 (2016): 1-6.
- [17] Rohit Kumar " Advanced Tools and Techniques for Re-configurable Processor Architectures" MATRIX Academic International Online Journal of Engineering and Technology 1.2 (2016): 1-6.
- [18] Bhullar, Rohit K., et al. "Intelligent stress calculation and scheduling in segmented processor systems using buddy approach." Journal of Intelligent & Fuzzy Systems 32.4 (2017): 3129-3142.
- [19] Prof G.Ramaswamy, Vuda Sreenivasarao, Dr.P.Ramesh, D.Ravi Kiran, "A Novel Approach for Human Identification through Fingerprints", International Journal of Computer Applications (IJCA), Volume 4 - No.3, July 2010.
- [20] Kumar, Rohit, et al." Improved Speech Recognition, Classification, Extarction using Conditional Random Field with Kernel Approach " International Journal of Computational Intelligence Research, 13.6 (2017).